



**COLORADO TIMBERLINE**  
9911 E. 47th AVENUE  
DENVER, CO 80238 USA  
ATTN: DAN GREENE

October 2, 2009

**IDENTIFICATION SUBMITTED BY CLIENT**

DESCRIPTION : DIGITAL PRINT  
COLORS : BLACK WITH PRINT

**TEST RESULTS**

**WEARING APPAREL FLAMMABILITY: 16 CFR PART 1610 (AS AMENDMENT IN 2008)**

Plain Surface			Face		
Original			After One Drycleaning / Laundering per AATCC 124		
Preliminary Test for Plain Surface Samples Only			Preliminary Test for Plain Surface Samples Only		
Length	Burn Characteristics	Time (s)	Length	Burn Characteristics	Time (s)
1	DNI	---	1	DNI	---
2	DNI	---	2	DNI	---
Width	Burn Characteristics	Time (s)	Width	Burn Characteristics	Time (s)
1	DNI	---	1	DNI	---
2	DNI	---	2	DNI	---

Final Test			Final Test		
Test Burn Dir: X Length	□ Width	Test Burn Dir:			
	Burn Characteristics	Time (s)		Burn Characteristics	Time (s)
1	DNI	---	1	DNI	---
2	DNI	---	2	DNI	---
3	DNI	---	3	DNI	---
4	DNI	---	4	DNI	---
5	DNI	---	5	DNI	---
Average			Average		

**Classification: X Class 1, Normal Flammability,  
Class 2, Intermediate Flammability, Raised surface  
Class 3, Rapid and Intense Burning,  
No Evaluation for informational purposes only.**

**Explanation of Flammability Results:**

- \*IBE* Ignited, but extinguished, the asterisk (\*) denotes a burn that goes under the cord without breaking the cord.
- DNI* Did not ignite
- IBE* Ignited but extinguished
- \* 0.0 SFBB* Time in seconds, surface flash base burn possibly starting at the point of impingement. The asterisk is accompanied by the following: "Unable to make absolute determination as to source of base burns." This note is added to the result of any specimen if there are questions as to origin of the base burning. It does not qualify as a base burn under the current interpretation of CFR 1610.
- poi*
- 0.0 SF only* Time in seconds, surface flash only. No damage to the base fabric.
- 0.0 SFBB* Time in seconds, surface flash base burn. Base starts burning at points other than that point of impingement.
- 0.0 SFBB poi* Time in seconds, surface flash base burn starting at the point of impingement.
- SF pw* Surface flash, part way. No time shown because the surface flash did not reach the cord.
- SF uc* Surface flash, under the cord, but does not break the cord.
- SF poi* Surface flash, at point of impingement only (equivalent to "did not ignite" for plain surfaces).

**IF YOU NEED ASSISTANCE IN INTERPRETING THESE TESTS RESULTS  
OR IF YOU HAVE ANY QUESTIONS, PLEASE FEEL FREE TO CALL:  
CUSTOMER SERVICE DEPT.**

**INTERTEK**



Eduardo Palomo  
Senior Client Manager

**GG**